

Eaton SDR-REXT-G2-OR

Catalog Number: SDR-REXT-G2-OR

Eaton external burglar alarm siren, Sounder external radio orange lens

General specifications



Product Name	Catalog Number
Eaton external burglar alarm siren	SDR-REXT-G2-OR
EAN	Product Length/Depth
5060096853640	80 mm
Product Height	Product Width
300 mm	280 mm
Product Weight	Compliances
1.8 kg	CE marking

Product specifications

Operating humidity - max

95 %

Degree of protection (NEMA)

Other

Compliance

Independently certified to EN50131 & INCERT

Operating temperature - min

-25 °C

Remote self test function

No

Supply

6 V

Mounting Method (ETIM)

Surface mount

Current normal

0.25 mA

Enclosure/lens color

Orange

Low-volume mode

Yes

Built-in transformer

Yes

Typical battery life

24 monthly

Radio frequency

868.6625MHz

Operating temperature - max

60 °C

Replacement battery code

SDR-R-BAT1

Degree of protection (IP)

IP65

EN 50131 Security Grade

2

Type Of Tone

Resources

Catalogues

[External siren - Declaration of conformity](#)

[Sounder free printing service \(Process for installers\)](#)

[External siren flyer](#)

[Residential and commercial security systems catalogue](#)

[Scantronic radio devices battery list](#)

[Sounder free printing service \(Process for distributors\)](#)

[External siren - Datasheet](#)

Multi-tone

Type Of Tone (ETIM)

Fast beat

Electricity consumption

0 A

Cut-off period

Choose 5 secs, 3 mins or (default) 15 mins

Connection

Radio

Type of current

DC

Housing material

Plastic

Sounder output

100 dB

Sounder type

External

Enclosure material

ABS (cover) Polycarbonate (lens)

Free space radio range

500 m

Environmental class

Class IV



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)